

AnyRead™ JBR-100/200/300

SPECIFICATION

Dimensions	46mm(W) × 95.8mm(L) × 26.5mm(H)	
Weights	Under 75g(including battery)	
Barcode Module	1D&2D CMOS Imager	
Display	0.95Inch 65k OLED(96×64)	
Buttons	Scan key, Left key, Right key, Reset	
LEDs	LED : 5EA	
Bluetooth	Bluetooth Version 2.1 + EDR, Class2, HID/SPP Profile	
USB	Micro USB	
Memory	8M Serial Flash Memory, 1MB Flash 128KB RAM	
MCU	STMICRO STM32F205RBT6	
NFC Protocol	ISO 14443A, ISO 14443B, ISO 15693, Mifare 1K, FeliCa	
NFC Chipset	TRH-033MS of 3Alogics(Korea)	
Battery	DC 3.7V, 720mAh, Li-polymer	
Operating Time	About 8 hours	
Charging	Via Micro USB connector	
Operation Temp	-10 ~ 50℃	
Storage Temp	-20 ~ 60℃	
Humidity	5 ~ 85%	
Drop Spec	1.5m	
Water/dustproof	IP54	
FEATURE	•Stylish design and color •Optional 1D (Laser, CCD) and 2D (CMOS) •Class 2 Bluetooth with SPP/HID profiles •NFC supported models : ISO 14443 A/B, ISO 15693 •LED : 5EA •0.95Inch 65k OLED(96×64) display •Two alarm types : Beep sound and Vibration •Stores 500,000 product records •Rechargeable Li-Poly Battery	